

B2
(cont'd)
Sub
D1

generating a signal on a first output terminal of the integrated circuit according to the comparison to control the temperature of the integrated circuit, wherein the signal is asserted when the measured temperature is greater than the first limit value, and wherein the signal on the first output terminal is deasserted when a control location on the integrated circuit is accessed or when the measured temperature goes below a lower limit value, according to a programmable mode of operation.

14. Canceled.

B3 Sub
D1

15. (Amended) The method as recited in claim 13 wherein the asserted signal is used to inhibit a cooling device to control the temperature of the integrated circuit.

16. Canceled.

17. Canceled.

19. Canceled.

B4 Sub
D1

20. (Amended) A method comprising:
measuring a temperature of an integrated circuit with a temperature sensor, the temperature sensor being a circuit within the integrated circuit;
comparing the measured temperature to a first limit value stored in the integrated circuit;
generating a signal on a first output terminal of the integrated circuit according to the comparison to control the temperature of the integrated circuit; and
accessing a control location in the integrated circuit to cause the signal to be deasserted.

21. (Amended) The method as recited in claim 13 wherein the asserted signal causes assertion of an interrupt and wherein a sequence of instructions, responsive to the asserted interrupt, activates a cooling device.

B5 Sub
D1

23. (Amended) A method comprising:

measuring a temperature of an integrated circuit with a temperature sensor, the
temperature sensor being a circuit within the integrated circuit;
comparing the measured temperature to a first limit value stored in the integrated circuit;
and
generating a signal on a first output terminal of the integrated circuit according to the
comparison to control the temperature of the integrated circuit;
comparing the measured temperature to a second limit value stored in the integrated
circuit; and
asserting a second signal on a second output terminal of the integrated circuit when the
measured temperature is above the second limit value, thereby indicating that
temperature has exceeded a safe limit.

B₅
(contd)

Sub
D₁